

Hearing Protection

uvex earmuff range



uvex x

The uvex x satisfies all the demands of an earmuff which must protect against extreme high noise exposure levels. The unique shape of the uvex x matches the requirement for perfect protection in extremely noisy environments. The small size and round design provides the security of perfect fitting, very high attenuation, low weight and comfortable pressure. The uvex x is the optimum in terms of comfort and efficiency for earmuffs in very noisy environments.

| | |
|--------------------|-----------|
| Art.no. | 2500.030 |
| Colour | blue |
| Weight | 220 g |
| Retail unit | 1 earmuff |

| SNR: 36 dB(A) | | | H: 38 dB(A) | | M: 34 dB(A) | | L: 26 dB(A) | | |
|------------------|------|------|-------------|------|-------------|------|-------------|------|------|
| f/Hz | 125 | 250 | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 |
| Insulation dB(A) | 20,9 | 29,1 | 35,7 | 41,6 | 39,4 | 43,0 | 41,7 | 42,4 | 42,4 |
| SD dB(A) | 3,5 | 2,2 | 3,1 | 2,5 | 2,9 | 2,7 | 2,2 | 3,3 | 3,7 |
| APV dB(A) | 17,4 | 26,9 | 32,6 | 39,1 | 36,5 | 40,3 | 39,5 | 39,1 | 38,7 |

uvex xV

The fluorescent surface of the headband reflects the light, uvex xV makes the wearer visibly more noticeable.

| | |
|--------------------|--------------------|
| Art.no. | 2500.031 |
| Colour | fluorescent yellow |
| Weight | 225 g |
| Retail unit | 1 earmuff |

| SNR: 36 dB(A) | | | H: 38 dB(A) | | M: 34 dB(A) | | L: 26 dB(A) | | |
|------------------|------|------|-------------|------|-------------|------|-------------|------|------|
| f/Hz | 125 | 250 | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 |
| Insulation dB(A) | 20,9 | 29,1 | 35,7 | 41,6 | 39,4 | 43,0 | 41,7 | 42,4 | 42,4 |
| SD dB(A) | 3,5 | 2,2 | 3,1 | 2,5 | 2,9 | 2,7 | 2,2 | 3,3 | 3,7 |
| APV dB(A) | 17,4 | 26,9 | 32,6 | 39,1 | 36,5 | 40,3 | 39,5 | 39,1 | 38,7 |

