

# Work positioning

**AZ 002**  
galvanized steel  
opening: 18 mm  
weight: 220 g

**AZ 003**  
aluminium  
opening: 20 mm  
weight: 160 g

**AZ 004**  
aluminium  
opening: 22 mm  
weight: 180 g  
twist lock

**AZ 040**  
aluminium  
opening: 23 mm  
weight: 80 g

**AZ 041T**  
aluminium  
opening: 23 mm  
weight: 100 g  
twist lock

**AZ 020**  
galvanized steel  
opening: 23 mm  
weight: 230 g

**AZ 021T**  
galvanized steel  
opening: 23 mm  
weight: 250 g  
twist lock

**AZ 030**  
aluminium,  
galvanized steel  
opening: 23 mm  
weight: 200 g

**AZ 031T**  
aluminium,  
galvanized steel  
opening: 23 mm  
weight: 200 g  
twist lock

**AZ 050**  
galvanized steel  
opening: 23 mm  
weight: 360 g

**AZ 051T**  
galvanized steel  
opening: 23 mm  
weight: 360 g

**NEW!**  
**AZ 002AS**  
aluminium,  
opening: 24 mm  
weight: 215 g

**AZ 060**  
galvanized steel  
opening: 21 mm  
weight: 380 g

free ending of the rope

adjuster of the rope length  
light alloys

kernmantle polyester rope  
Ø 14 mm

protecting tube

**PROT 3**  
**WORK POSITIONING DEVICE**

EN 358

Ref.: AF 130 xx (xx - length)

Standards:  
AF 130 02 - length 2 m  
AF 130 03 - length 3 m  
AF 130 04 - length 4 m  
AF 130 05 - length 5 m  
AF 130 10 - length 10 m  
AF 130 15 - length 15 m  
AF 130 20 - length 20 m  
Other lenghtes on request.