

GENERAL PRODUCT SPECIFICATION

Date	03-31-08	Replaces	06-06-06	No. Pages	1

D 1 .	D
Product	Description:

UN100-E

Item No.

Style	Pads; perforated on centerline for dividing in half for smaller applications.			
	71			
Item Size (each)	41 cm x 51 cm			
Color	Green			
Composition	Polypropylene >98%, Surfactant < 1.0%, color pigment < 0.1 %			
Structure	96% natural white meltblown nonwoven fibers(<10 microns)			
	4% white spunbond nonwoven coverstock(<15-30 microns)			
Technology	Meltblown + spunbond			
Absorbency	Universal (Hydrophilic + Oleophilic)			
Bonding	Bonded (staggered pattern) + Mechanical entanglement			

Intended Application Chemical & Static Resistant Sorbent for Water, Oil, or Solvent Base Liquids
--

Absorbency Capacity	88 l per bale (saturated; medium viscosity-12.5x)

Packaging Description:

Package configuration	1-Case	Pkg. Weight	7.1 kg (6.1 kg)
Items per Package	1-Bale / Case	Pkg. Dimensions	53cm x 43cm x
			44cm H
Container type	Carton		

Physical Properties;

<u>Parameter</u>	SPC Test Method	<u>Units</u>	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002	G/M2	295	30
Caliper	SPCTM-020	mm	4.5	0.5
Absorbency** (med	SPCTM-004B	gL/gS	12.5	2
visc)				
Tensile Strength	SPCTM-007	daN	14	1.4
Color	Visual		Green	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. ** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,
	Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer.
	Claims for non-conformance of goods must be made within 60-days of delivery.