

# Technical specs

## QUARTZUP3 - QUARTZ UP III

**Name:**

ROTOR® ADJUSTMENT SAFETY HELMET

**Size:**

Adjustable

**Colour:**

Blue - Green - Orange - Red - White - Yellow



CE 0082

**Description :**

UV-resistant high density polypropylene (PP) safety helmet. Polyamide harness: 3 textile bands with 8 fixing points. Foam sweat band. Innovative adjustable ROTOR® system: head sizes 53/63 cm. 2 possible positions of the headband (high/low) for better comfort. Electrical Insulation up to 1000 V.A.C. or 1 500 V.D.C. This helmet may receive the following accessories: JUGALPHA, DYNAMIC JUGALPHA, MENTALPHA. BASGAMMA ou BASALPHA

**Materials:**

Polypropylene (PP)

Weight : 332 g

**Strong points:**

Rotor® adjustment..

2 positionings of the head measurement : Optimized comfort.

**Instructions for use:**

The helmet is made so that the energy released after a shock is absorbed by partial destruction or damage of the cap and harness, even if such damage is not immediately noticed, it is recommended to replace any helmet having being subject to a strong shock.

In order to ensure enough protection, this helmet should be adapted or adjusted to the users head size. We should draw the users attention also on the eventual hazard of modifying or removing one of the original parts of the protective helmet, except for the modification and removal type recommended by the helmet manufacturer. Helmets should not be adapted in any case for setting accessories according to a procedure not recommended by the helmet manufacturer. Do not apply paints, solvents, adhesives or stickers on it, except for those recommended by the instructions of the helmet manufacturer.

**Limits to use:**

In order to ensure effective protection, this helmet should be worn with its peak forward (sit in straight position) and it should be adjusted to the user's head size (not fit to loose or to squeeze) to by its adjustment system serrated roller screwing-unscrewing located at the rear of the helmet (size 53-63 cm).The helmet life is affected by several factors, such as cold, heat, chemical products, sun light or misuse. A daily check should be performed in order to identify any sign of rendering (cracks, flaws) the helmet, its harness and accessories fragile. Any helmet having been subject to a strong shock or having wear signs should be replaced. If it has no defaults, it is therefore proper for the intended use. The manufacturing date is marked inside each helmet. Under normal usage conditions, this protective helmet should provide proper protection for 2 up to 3 years after the first usage, or 5 years according to the manufacturing date.

This helmet does not include any substance known to be susceptible of causing allergies. However if a sensitive person has an allergic reaction, it should therefore leave the hazardous area, remove the helmet and ask for medical advice.

**Instructions for storage:**

When it is not used anymore or during transportation, the helmet should be stored in a dry cool place away from light, frost and in a location granting that no chemical product or sharp object bends it by falling above.



**DELTA PLUS GROUP**

La Peyrolière - B.P. 140 - 84405 APT Cedex - France  
www.deltaplus.fr



# Technical specs

## QUARTZUP3 - QUARTZ UP III

### Instructions for cleaning / maintenance:

This protective helmet may be cleaned and disinfected by means of a cloth impregnated in a low concentration cleaning solution. One shall not use any abrasive or corrosive chemical product. If this helmet cannot be cleaned by using this method, it should be replaced.

### Performances :

This helmet complies with the European directive 89/686, notably regarding ergonomics, innocuousness, comfort and ventilation, and with EN397:1995/A1:2000 (-30°C / +50°C) & 440 V AC standard). standard & EN50365:2002 (Class 0).

-30°C : Very low temperature

The helmet keeps its performance above these temperatures